

# Bung Adapters & Accessories

## For Industrial Drum, IBC (Tote) and Tank Bung Holes

### Bung ThreadConverters™ Convert Buttress or Mauser coarse threads to 2" NPT

**Benefits:** Permits easy and rapid mounting of fume filters, funnels, depth gauges, pumps, mixers and other drum equipment into drums, IBC's (Totes) or any container with US or European coarse bung threads. Temp. Range: -5°F min. to +120°F max

<b>DM-55BCF/B</b> (US)	ThreadConverter™ hex Buttress male to 2" NPT female thread, HDPE
<b>DM-55BCF/B6</b> (US)	ThreadConverter™ hex Buttress male to 2" NPT female thread, stainless
Buttress Specifications:	2.525" OD x 1.812" H x 2.625" dia. flat-to-flat, Thread: 5mm pitch
<b>DM-55BCF/FB2</b> (US)	ThreadConverter™ Buttress female bung thread to 2" NPT male thread
Buttress Specifications:	3.0" OD x 2.875" H x 1.625" ID, 5.0 mm pitch, reinforced nylon, Santoprene
<b>DM-55BCF/M</b> (European)	ThreadConverter™ hex Mauser male bung thread to 2" NPT female thread
Mauser Specifications:	2.710" OD x 1.35" H x 3.0" dia. flat-to-flat, Thread: 6.0 mm, HDPE, EPR
<b>DM-55BCF/MF</b> (European)	ThreadConverter™ hex Mauser female bung thread to 2" NPT male thread
Mauser Specifications:	3.0" OD x 2.75" H x 60mm thread x 6.0 mm pitch, HDPE
<b>DM-55BCF/FBC</b> (Cam-Lock)	ThreadConverter™ Buttress female bung thread to 2" Cam-Lock
Buttress Specifications:	3.0" OD x 3.25" H x 1.625" ID, 5.0 mm pitch, reinforced nylon, Santoprene



### Bung ThreadReducer™ Converts 2" NPT threads to smaller ID, NPT thread sizes, 1/2" to 1.5"

**Benefits:** Hex bung adapter permits mounting of a variety of hoses or equipment thread sizes, from 1/2" to 1.5" into 2" bung ports, drum, tote or tank bungs, or any container or process equipment with 2" NPT threads. Weight, PP 2 oz. or SS 9 oz.

Product Code	Specifications	Material
<b>DM-55BTR2-05</b>	2.0" M-Npt - 1/2" F-Npt, bung thread reducer	Polypropylene or 316 stainless steel
<b>DM-55BTR2-75</b>	2.0" M-Npt - 3/4" F-Npt, bung thread reducer	Polypropylene or 316 stainless steel
<b>DM-55BTR2-100</b>	2.0" M-Npt - 1.0" F-Npt, bung thread reducer	Polypropylene or 316 stainless steel
<b>DM-55BTR2-125</b>	2.0" M-Npt - 1.25" F-Npt, bung thread reducer	Polypropylene or 316 stainless steel
<b>DM-55BTR2-150</b>	2.0" M-Npt - 1.5" F-Npt, bung thread reducer	Polypropylene or 316 stainless steel



### Bung ThreadGuard™ Permanently protects plastic drum Npt threads and equipment threads

**Benefits:** Stops stripping and wearing of sensitive plastic threads due to constant use in steel bung holes. Extends useful life of items like depth gauges, fume filters, pumps and other plastic bung mounting equipment. Permits easier equipment mounting. Items can be permanently sealed in ThreadGUARD™.

Product Code	Specifications	Material
<b>DM-55BTG/S6</b>	2.0" Ht. x 2.85" OD, 2" NPT, ThreadGuard	316 stainless steel, Wt. 9 oz.
<b>DM-55BTG</b>	2 3/4" Ht. x 2.75" OD, 2" NPT, ThreadGuard	zinc plated steel, Wt. 9 oz.



### Bung TubeGuard Adapter Permits process tube to be safely secured in drum bung

**Benefits:** 2" NPT bung TubeGuard adapter, permits tube mounting in drum bung holes for pump tubes, filling tubes, heating tubes, shafts, etc. to be safely secured inside a drum bung hole for tube and thread protection. Available in a wide variety of tube fitting sizes. Specify tube OD or TubeGuard bore-opening size & material of construction: polypropylene or stainless steel.

Product Code	Specifications	Material
<b>DM-55BTA/SS1630</b>	1.375" Ht. x 1.630 ID x 2.0" MPT TubeGuard	316 stainless steel, Wt. 0.8 lb
<b>DM-55BTA/SS__ ID to Spec:</b>	1.375" Ht. x Spec. ID x 2.0" MPT TubeGuard	316 stainless steel, Wt. 1.2 lb
<b>DM-55BTA/PP 1630</b>	1.375" Ht. x 1.630 ID x 2.0" MPT TubeGuard	polypropylene, Wt. 0.4 oz.
<b>DM-55BTA/PP__ ID to Spec:</b>	1.375" Ht. x Spec. ID x 2.0" MPT TubeGuard	polypropylene, Wt. 0.4 oz.



### Safety SplashCap™ Improve bung entry mixing Quality Control in drums and totes

**Benefits:** SplashCaps™ help prevent exposure to airborne, moisture, dust, hazardous liquid splash-back, fume exposure, contamination etc. Helps seal bung hole during bung mixing or cleaning with DM-55MRT rinse tube.

Product Code	Specifications	Material	Wt.
<b>DM-55SCC/MRT</b>	rinse tube cleaning with DM-55MRT	plated steel	0.2 lbs.
<b>DM-55SCC/SD2__</b>	steel drum mixing with DM-55ADH/A	polyethylene	0.1 "
<b>DM-55SCC/PDB2__</b>	plastic drum mixing with DM-55ADH/A	polyethylene	0.1 "
<b>DM-55SCC/BAS__</b>	bung mount mixing with DM-55BAS	polyethylene	0.1 "



DRUM-MATES® equipment assemblies are provided as separate components, each sold on a separate basis. Ask for literature on DRUM-MATES® drum & IBC mixers, drum tumblers, drum & IBC pumps & hand nozzles. DRUM-MATES® Inc., Drum Mixer & Pump Div., Tel: 1-800-621-3786 and 609-261-1033, Fax: 609-261-1034