

Hi-Flow Polypropylene Hand Nozzles

DM-150HFR, 1.5" or DM-200HFR, 2"

For All High Flow Hand Transfer Tasks - Pump or Gravity Feed

Benefits & Features...

- ⇒ Careful fluid control for increased operator & environmental safety
- ⇒ Extended reach with 1½" ID x 8.0" length spout
- ⇒ Excellent non-flammable chemical compatibility for most liquids
- ⇒ Fiber reinforced polypropylene for heavy duty applications
- ⇒ Helps prevent spillage during critical liquid transfer operations
- ⇒ Simplifies liquid filling or bulk transfer into smaller containers



Hi-Flow Hand Transfer Nozzle

DM-150&200HFR Nozzle Hi-Flow, Heavy Duty, Manual Shut-off, Precision Control

Materials of Construction: Polypropylene, Teflon wetted parts, Viton seals, external stainless steel fasteners
 Flow Rate: 64 Gpm at 10 psi, 200 Gpm at 40 psi, 680 Gpm at 150 Psi
 Pressure Range: 0 – 150 PSI, (0 – 1050 kPa)
 Temperature Range: 0°F - to 125°F
Optional Components: Full range of replacement parts
 Hose Barb Assembly, 1.5 or 2.0 PP hose barb
 Quick Disconnect Cam-Lok Fittings

Item No.	Part Number	Description
1	V20017	3/8X16X4 BODY BOLT
2	V20018	3/8 BODY LOCKWASHER
3	V20019	3/8-16 BODY NUT
4	V20020	1/4 X 1/2 HANDLE BOLT
5	V20021	HANDLE WASHER
6	V20060	TEFLON THRUST BUSHING
7	V20151	STEM 150-200
8	V20152	ANGLE HANDLE 150-200
9	V20159	UPPER STEM BUSHING
10	V20163	O-RING
11	V20254	VALVE BODY 150-200
12	V20255	VALVE BALL
13	V20257	1-1/2" END PLATE
14	V20258A	1 1/2" VALVE SEAT
15	V20262	ANGLE END FLANGE 1-1/2"
16	V20264	VALVE O-RING 150-200
17	V20166	NOZZLE PIPE 1-1/2" X 8"
N/S	VL100	PRESSURE LABEL

Parts List



Ask for literature on DRUM-MATES® drum & tote mixers, drum tumblers, drum & tote pumps & hand nozzles.
 DRUM-MATES® Inc., Liquid Process Equip. Div., Tel: 1-800-621-3786, Tel: 609-261-1033, Fax: 609-261-1034