

Lever Hand Pump, Extreme Duty

Sanitary & Industrial Models

Transfers most Low to High Viscosity Liquids, up to 4000 Cps

Features

- Ideal for applications with low or high viscosity liquids up to 4000 Cps
- Ergonomic lever stroke maximizes comfort, minimizes Operator stress
- Designed for long-life and heavy duty use in factory, shop, dock or field
- 2" Npt bung mount (Global ThreadConverters available separately)
- Telescoping pick-up tube will adapt to varying drum, tote or tank depths



DM-55LHP-SST
Sanitary Duty Model

Model Specifications & Options

DM-55LHP-S Series Pumps - General Specifications

- Pump dispenses 11 Strokes per gal., 12 ounces per stroke
- Suitable for 15 gal, (56L) 30 gal (113L) & 55 gal (210L) drums
- Light weight permits easy handling & transfer, Wt. 7.0 lbs. (3.2 Kg.)

Part # DM-55LHP/SST, Sanitary Grade Model

For any liquids chemically compatible with Wetted Materials of Construction: 304 grade stainless steel and Teflon (PTFE).

Part # DM-55LHP-SHV, Industrial Grade Model

For oil based liquids, oils, paraffin, fuels, kerosene, solvents, cutting lubricants, or for any liquids chemically compatible with Wetted Materials of Construction: Zinc plated steel, HDPE, Neoprene, Delrin



DM-55LHP-SHV, Industrial Duty Model
Extra angled style spout, Supplied Free

Optional Accessories

DM-55LHP/SST-SK, Pump Service Kit of all wetted-parts

DM-100PPH/PVC10DW, Extension filling wand and hose

DM-55LHP/SLC, Flow output shaft clamp, controls flow volume



Drum-Mates, Inc., Process Equip. Div.

E: info@drummates.com, www.drummates.com

Tel: 609-261-1033, Fax: 609-261-1034