1.5" Xtreme Duty Hand Nozzle

Model DM-790HFR Series, For Pressure or Gravity Transfer

Benefits & Features...Stainless, Teflon, Aluminum!

- Prevents spillage during critical liquid dispensing, refilling
- Careful fluid control for operator & environmental safety
- Ergonomic comfort with long reach 9" spout, 90° pour angle
- Simplifies batch or bulk transfer into drums, containers, tanks
- For Chemicals, Solvents, Water, Overwing Refueling, etc.
- Liquids compatible with Aluminum, Stainless and Teflon
- Features: Hold-Open trigger catch and XP cable lanyard ring



Model # DM-790HFR Specifications and Features

P# DM-790HFR/**AMT**S15:



P# DM-790HFR/**AMV**S15: Hose Inlet: Dispensing Mode & Spout: Dispensing Flow Rate: Maximum Pressure: Temperature Range: **NET Weight:**

Optional Service Kit

Materials: Aluminum, stainless steel, **Teflon** (wetted parts) Materials: Aluminum, stainless steel, Viton (wetted parts) 1.5" female NPT (or 1.5" Optional Accessory - SS Hose Barb) Manual spring loaded shutoff, stepped hold-open, 9" spout Approximate 60 GPM, (228 liters per minute) 50 PSI, (350 kPa) 15°F - to 120°F (or up to 155°F with operator protection)

6.5 lbs, (2.95 Kg.)

Includes seals and gaskets for regular nozzle maintenance

Parts List	
1	Body, AL = Aluminum
2	Handle, AL
3	Cap, AL
4	Cap gasket
5	Spout, AL
6	1.5" Hose barb, opt. access.
7	Plunger, SS = Stainless Steel
8	Large disc holder, SS
9	Large disc, Teflon
10	Large disc nut, SS
11	Large disc washer, SS
12	Spring, stainless
13	Small disc, Teflon or Viton
14	Small disc guide, SS
15	Small disc holder, SS
16	Stuffing box, SS
17	Packing gland, SS
18	Packing nut, SS
19	Packing, Teflon or Viton
20	Groove pin, SS



